

Material Safety Data Sheet (MSDS)

Part 1: Chemicals and Corporate Identification

Chemical Name (Chinese): E962F Low Odor Self-Drying Insulating Varnish

Common or trade names of chemicals: varnish, insulating varnish

Chemical formula: mixture

Company Name: Zhuhai Changxian New Material Technology Co., Ltd.

Address: Langwan Road, Fine Chemical Industrial Zone, Gaolan Port Economic Zone, Zhuhai City

Postal code: 519050

Email address: szwkb@changxiankeji.com

Fax number: +86-755-26689087

Telephone numbers: +86-755-26852596 +86-755-26852597 +86-755-26864069

Company emergency hotline: +86-13802269905

National Emergency Hotline: +86-532-83889090

Part 2: Hazard Overview

Emergency Overview: Flammable liquids and vapors that may cause drowsiness or dizziness; inhalation is harmful.

GHS Hazard Categories: Flammable Liquids, Category 2; Skin Irritation/Corrosion: Category 2; Reproductive Toxicity: Category 2; Specific Target Organ Toxicity: Single Exposure, Category 3 (Anesthetic Effect); Specific Target Organ Toxicity: Repeated Exposure, Category 2; Inhalation Hazard: Category 1; 2; Hazards to the Aquatic Environment - Acute Hazards, Category 2; Hazards to the Aquatic Environment - Long-Term Hazards, Category 3

Label elements are in accordance with GB 15258-2009 (Regulations for the Preparation of Safety Labels for Chemicals).

Pictograms:



Warning word: Danger

Hazard statement: Flammable liquid and vapor; harmful if swallowed; harmful if inhaled; causes skin irritation; harmful to aquatic life.

Prevention instructions:

Preventive measures Keep away from sparks, open flames, and heat sources. Keep containers tightly sealed. Use explosion-proof electrical, ventilation, and lighting equipment, and use machinery and tools that do not generate electrical sparks. Take anti-static measures. Wear protective gloves, safety glasses, and a face shield. Avoid contact with eyes and skin; wash thoroughly after handling. Avoid inhaling vapors or fumes. Do not release into the environment.

Incident Response: In case of fire, use foam, carbon dioxide, dry powder, or

Material Safety Data Sheet (MSDS)

sand to extinguish the fire. If inhaled, move to a well-ventilated area to rest. Spray water to keep containers in the fire area cool until the fire is extinguished. If skin (or hair) comes into contact: Immediately remove contaminated clothing, wash thoroughly with soap and water, and take a shower. Secure storage Store in a cool, dark, and well-ventilated warehouse. Keep containers tightly sealed. Maintain a low temperature.

Waste disposal Before disposal, consult relevant national and local regulations, or use incineration.

Physical and chemical hazards:

It is flammable, and its vapor can form an explosive mixture when mixed with air.

Health hazards: It has an irritating effect on the skin and mucous membranes, and high concentrations have an anesthetic effect on the central nervous system.

Acute poisoning: Inhalation of high concentrations of this product in a short period of time can cause obvious irritation symptoms to the eyes and upper respiratory tract, as well as headache, dizziness, nausea, etc.

Chronic effects: Long-term exposure can cause neurasthenia syndrome, and prolonged skin contact can cause dryness, cracking, and dermatitis.

Part 3: Ingredient/Composition Information

Pure Mixtures

Concentration of substance components CAS NO

Modified polyester resin 35-50% 25135-73-3

Ether ester solvent 15-30% 108-65-6

Hydrocarbon solvents 20-30% 64742-48-9

Other additives 3% (Trade secret)

Part 4: First Aid Measures

Inhalation: Immediately move to fresh air.

Skin contact: Remove contaminated clothing and wash skin thoroughly with soap and water.

Eye contact: Immediately open the upper and lower eyelids and rinse with running water or saline solution for at least 15 minutes, then seek medical attention.

If ingested: Rinse mouth with water and seek medical attention.

Part 5: Firefighting Measures

Extinguishing agents: Foam, carbon dioxide, dry powder, and sand can be used to extinguish fires.

Special hazards: Flammable; its vapor forms an explosive mixture with air. It

Material Safety Data Sheet (MSDS)

can react with oxidizers.

Firefighting Precautions and Protective Measures: Firefighters must wear gas masks and full-body fire suits and fight the fire from upwind. Move containers from the fire area to an open space if possible. Spray water to keep containers in the fire area cool until the fire is extinguished. If containers suddenly make unusual noises or exhibit unusual phenomena, evacuate immediately.

Hazardous combustion products: CO , CO₂

Part 6: Leakage Emergency Response

Personnel protective measures: Immediately evacuate personnel from the contaminated area to an upwind location and isolate the area, strictly restricting access. Eliminate ignition sources. Emergency responders are advised to wear self-contained positive pressure breathing apparatus and anti-static work clothes. Cut off the leak source if possible.

Environmental protection measures: Prevent leaked materials from entering water bodies, sewers, basements, or confined spaces.

Methods for containing and cleaning up spilled chemicals and the disposal materials used:

Small leak It can be adsorbed or absorbed by sand or other non-combustible materials.

Massive leak Construct dikes or dig pits to contain the vapors; cover with foam to reduce vapor hazards.

Part 7: Handling and Storage

Operating Precautions: Operate in a closed system with enhanced ventilation. Operators must be specially trained and strictly adhere to operating procedures. It is recommended that operators wear self-priming filter respirators (half-face masks) and anti-static work clothes. Keep away from sources of ignition and heat; smoking is strictly prohibited in the workplace. Use explosion-proof ventilation systems and equipment. Prevent vapor leakage into the workplace air. Avoid contact with oxidizers and alkalis. Provide appropriate types and quantities of fire-fighting equipment and leakage emergency response equipment. Smoking is strictly prohibited at the work site. Avoid inhalation of high concentrations.

Storage Precautions: Store in a dark, cool, and well-ventilated warehouse. Keep away from fire and heat sources. Keep containers sealed. Shelf life is generally six months from the date of production at temperatures below 25° C. Warehouse lighting and ventilation systems should be explosion-proof, with switches located outside the warehouse. The use of machinery and tools that may generate sparks is prohibited. The storage area should be equipped with spill response equipment.

Material Safety Data Sheet (MSDS)

Part 8: Exposure Controls/Personal Protection

Exposure limit: 100 mg/m³ (skin)

Biological exposure limit: 1.5 g/g (creatinine liver)

Monitoring methods: Methods for determining toxic substances in the air

Engineering controls: The production process is closed, and ventilation is enhanced.

Respiratory protection: Wear a filter-type gas mask (half-face mask) for high-concentration exposure.

Eye protection: Wear chemical protective eyewear.

Body protection: Wear protective clothing against toxic substances.

Hand protection: Wear oil-resistant rubber gloves

Other protective measures: Smoking, eating, and drinking are prohibited at the work site. Shower and change clothes after work.

Part 9: Physical and Chemical Properties

Appearance and properties: Brown, semi-transparent liquid

Relative density (25 °C): 0.950 ± 0.03

(Generally, a 1° C increase in temperature results in a decrease in specific gravity of approximately 0.001, and conversely, a 1° C decrease in temperature results in an increase in specific gravity of approximately 0.001.)

Saturated vapor pressure (mmHg): 34/26.0 °C

(Ford Cup 4, seconds, 25° C): 16 ± 5.0

solid components (%): 40 ± 3.0

flash Point (° C) : 22

Ignition temperature (° C): 528

Explosive limit (lower limit), % (vol) : 1.0

(Maximum), % (vol) : 7.0

Main uses: Primarily used for coating or impregnating the surfaces of various electronic components such as transformers and coils.

Part 10: Stability and Reactivity

Stability: Stable

Incompatible materials: strong oxidizing agents, strong acids.

Conditions to avoid: open flame, high heat, static electricity

Polymerization hazard: Cannot occur

Decomposition products: carbon monoxide, carbon dioxide

Part 11: Toxicological Information

Material Safety Data Sheet (MSDS)

name	result	type	dose	Exposure
hydrocarbon solvents	LC50, inhalation	rats	118g/m3	4H
Ether ester solvents	TWA		50ppm	8H

Conclusion/Overview

Skin irritation or corrosion: No data available.

Eye irritation or corrosion: No data available.

Respiratory or skin allergies: No data available

Mutagenicity: No data available.

Carcinogenicity: No data available.

Inhalation hazards: No data available.

Part 12: Ecological Information

LC50 34.27 mg/L (96H) Blackhead Carp

Durability and Degradability: Biodegradability: Easily and rapidly biodegraded

Non-biodegradability: Photo-oxidation half-life in water (H): 321-1284

Photo-oxidation half-life (H) in air: 10^{-104}

Potential bioaccumulation: Based on the Kow value, this substance may have some bioaccumulation potential.

Soil mobility: Based on Kow values, this substance may have some mobility.

Part 13: Waste Disposal

Waste chemicals: Dispose of by incineration

Contaminated packaging: Return the containers to the manufacturer or dispose of them in accordance with relevant national and local regulations.

Waste Disposal Considerations: Waste generation should be avoided or minimized as much as possible. Significant quantities of residual product waste should be disposed of by a licensed waste management contractor, including residues and non-renewable products. The disposal of products, solutions, and their byproducts should comply with environmental protection, waste management regulations, and applicable local regulations.

Waste disposal methods: Before disposal, relevant national and local regulations should be consulted, and controlled incineration should be used.

Part 14: Transportation Information

Dangerous goods number: 33646

UN number: 1866

Packaging category: II

Material Safety Data Sheet (MSDS)

Packaging markings:



Packaging method: 20L or 200L/drum

Transportation Precautions: Transport vehicles should be equipped with appropriate types and quantities of fire-fighting equipment and leakage emergency handling equipment. Transportation is best done in the early morning or late evening during summer. Tank trucks used for transportation should have grounding chains, and perforated baffles can be installed inside the tank to reduce static electricity generated by vibration. Mixing or transporting with oxidizers, acids, alkali metals, amines, or food chemicals is strictly prohibited. Protect from exposure to sunlight, rain, and high temperatures during transportation. When stopping en route, keep away from sources of ignition, heat sources, and high-temperature areas. Vehicles transporting this item must have flame arresters on their exhaust pipes, and the use of machinery and tools that may generate sparks during loading and unloading is prohibited. When transporting by road, follow the prescribed routes and do not stop in residential areas or densely populated areas. When transporting by rail, shunting is prohibited .

Part 15: Regulatory Information

The following laws, regulations, rules and standards stipulate the corresponding provisions for the management of this chemical.

Occupational Disease Prevention and Control Law of the People's Republic of China : Classification and Catalog of Occupational Diseases: Not listed

Hazardous Chemicals Safety Management Regulations : Listed. List of Easily Explosive Hazardous Chemicals: Not listed. List of Key Monitored Hazardous Chemicals: Not listed. GB18218-2018 "Identification of Major Hazard

Installations of Hazardous Chemicals" (Table 1): Listed. Category: Flammable liquid, Critical quantity (t): 500

Labor Protection Regulations for Workplaces Using Toxic Substances : List of Highly Toxic Substances: Not Listed

Regulations on the Administration of Precursor Chemicals: Classification and Catalog of Precursor Chemicals: Not listed

International Conventions : Stockholm Convention: Not listed. Rotterdam Convention: Not listed. Montreal Protocol: Not listed.

Part 16: Other Information

Drafting and Revision Information: May 18, 2025, Technical Department

Training Recommendation: Please provide relevant training to users.

Disclaimer: The above information is not specific to this product and is for

Material Safety Data Sheet (MSDS)

reference only. No warranty is provided. It is believed that the above-mentioned industrial safety and hygiene procedures are generally feasible. However, users should assess for themselves whether the above recommendations are appropriate for their individual circumstances.